


Technical Data Sheet

Product Description

80 μ m Polyimide Tape

Construction



Typical Physical representative

Note: The following technical information and data should be considered

Properties and Performance Characteristics

For typical only and should not be used for specification purposes for reference Final using customer me considering by themselves.

| PRODUCT NAME | | | |
|---------------------|----------------|---------------------------------------|----------------|
| MODEL NO. | WE-PI80 | | |
| ITME | UNIT | SPEC | TEST METHOD |
| Total Thickness | Mm | 0.08mm \pm 0.001mm | GB7125-1999 |
| Substrate thickness | Mm | 0.060mm + 0.001mm | GB7125-1999 |
| Adhesion | N/25mm | 6.5 | GB/T72792-1998 |
| Tensile Strength | N/25mm | 160 | GB7753-1987 |
| Elongation | % | 70 | GB7753-1987 |
| Breakdown voltage | KV | 7.0 | GB7753-1987 |
| Heat Resistance | $^{\circ}$ C | -73 $^{\circ}$ C --+ 286 $^{\circ}$ C | GB/T7292-1998 |
| Length | M | 33 | - |
| Width | mm | - | - |
| Color | - | - | - |
| Liner | PET 50 μ m | - | - |

Feature

- Good for insulation
- Easy converting by die cut

Application idea

-Electric insulation Tape, insulation PCBA

For Additional

To request additional product information or to arrange for sales assistance, call +662-5142635
Address correspondence to : MATERIALONE (THAILAND) LIMITED.

MaterialOne (Thailand) Limited : 568/4 Soi Lat Phrao 112 (Aumsomboon) Lat Phrao Rd Phlappphla
Wang Thonglang Bangkok 10310 Thailand.

Important Notice

COMPANY MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of company standard products in a particular application. The materials to be bonded with the product. The surface preparation of those materials, the product selected for use the conditions in which the product is used. and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a company standard product. Given the variety of factors that can affect the use and performance of a company standard product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the company standard product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Limitation of Remedies And Liability

If the company products is proved to be defective, THE EXCLUSIVE REMEDY, AT COMPANY'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE COMPANY PRODUCT. COMPANY shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.