

## Polyethylene Protective Tape PG 700

### Product Data Sheet



#### Product Description

PG 700 features a very high tack adhesive system that help to provide protection on matt surfaces from scratches..

#### Applications

Designed for use as advertising transfer tape, and carpet masking. Also applicable to any rough surfaces.

#### Construction



Acrylic Adhesive  
Polyethylene Film

#### Technical Specifications (Based on 50μ Film)

Properties	Specifications	ASTM Test Method
<b>Adhesion</b>	680±60 g/25mm	D-3330
<b>Tensile</b>	>80 kg/cm <sup>2</sup>	D-882
<b>Elongation</b>	>150 %	D-882

#### Test Method

Adherend : Stainless Steel SUS 304 2B  
Tensile speed : 300mm/min  
Peeling angle : 90 degree

#### Available Physical Specifications

<b>Thickness</b>	40~130μ.
<b>Color</b>	Transparent Clear, Transparent Blue, Opaque Black & White. Other colors available upon request.
<b>Film Type</b>	Normal, UV Resistant (3 or 6 months) or Anti-Static
<b>Temperature Rating</b>	60 Degree Celsius

#### Storage

To be stored in places away from direct sunlight in conditions of 16°C-27°C and 40%-60% relative humidity.

## **Polyethylene Protective Tape PG 700**

---

### **Precautions**

- 1) Prior to its application, we recommend that applicants to duly inspect the adaptability of this product for its intended use. It should be your ultimate responsibility and decision to determine its functional usage on your products.
- 2) The performance of the protective film will also be dependent on the type adherend, environment, and conditions after application. It is recommended to do testing before changing the adherend products.
- 3) It should be noted that when the product is applied to plastic adherends with a plasticizer or surface-active adherends (electrolyzed, chemically treated, polished, etc.), the film may become difficult to release or may tend to leave deposits, as time passes.
- 4) Care should be taken to ensure that no traces of air bubbles are trap during the application process. As a consequence, it may leave traces.
- 5) Aforementioned problems may also arise when the product is stored for a long period of time after application.
- 6) Remove any dust, moisture or grease on the adherend before application.
- 7) Do not use this product outdoors unless it is of UV type.

---

### **Shelf Life**

This product is recommended to be used within 12 months from date of manufacture.

---

### **Usage**

All statements, information and recommendations contained herein is based upon tests or experience we believe to be reliable. The user shall determine the suitability of the product for their specific use.

---

## **Polyethylene Protective Tape PG 700**

---

### **Warranty and Limited Remedy**

PlasGard MAKES NO OTHER WARRENTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. The user is responsible to determine if PlasGard product is fit for their application and usage.

---