


*Excellent Adhesive Strength and Removability Double Coated Adhesive Tape*

## DAITAC #8800CH(W)

UL 969 approved [File No.MH-12834]

### CONSTRUCTION

Tape  
thickness  
  
0.145mm



Acrylic pressure  
sensitive adhesive  
Special non woven  
tissue  
Release paper liner  
("#8800CH" logo printed)

### CHARACTERISTIC

- Excellent adhesive strength to various plastic material and metal
- Excellent removability from various plastic and metal
- Dimensional stable backing provides excellent stability at tape application
- Excellent repulsion resistance and good heat resistance

### APPLICATION

- For many kind of parts used in electrical and electronics industry
- For mounting various recyclable materials in the industrial applications

### PROPERTY

		Unit	# 8 8 0 0 C H
Peel strength at 180° angle	S U S	N / 20mm	1 5 . 2
	A B S		1 5 . 2
	H I P S		1 5 . 2
	P P		1 3 . 0
Holdig power(40 , 1kg)		mm / h	1 >
Ball tack		No.	8
Adhesive strength at 90 ° angle and constant stress	SUS	mm / h	9
	23 , 0.3kg/10mm ABS		9
Removability	S U S		Good
After 7 days	A B S		Good
at 60 · 90%RH	H I P S		Good

### STANDARD SIZE

#8800CH:1000mm , #8800CHW:1060mm in max width / 50m in length