LABEL APPLICATOR APSeries





A Mech-Sensor combines with a sensor that automatically detects labels of different strokes to eliminate the need for manual alignment when you load labels.


- For pre-printed general roll labels. No special (punched or slit) labels or separators required.
- Supports use of label size from 18 x 20mm up to 60 x 100mm.

	-	ш			
		-	-	4	3
				Ш	
	- Ann	SHAIRE.	- NO	30	
- 80	Fines	0.0		_	
	11111111	100	THE REAL PROPERTY.		
	Mech-	0	-		



MODEL	LABEL GAP(mm)	LABEL SIZE(mm)		MAX. OUTSIDE
		STROKE	WIDTH	DIAMETER(mm
APN-30	2-3	18-60	20-30	100
APN-60			25-60	
APN-100			50-100	

The Mech-Sensor catches the label and automatically detects the stroke for smooth feeding.









A new slidable Mech-Sensor provides support for round, oval, and other non-rectangular shape labels.

- For eye-catching labels of various shapes that appeal to customers.
- Supports use of the label size from 20 x 20mm up to 60 x 100mm. For pre-printed general roll labels. No special (punched or slit) labels or separators required.




▲ Slidable Mech-Sens



it is in the center of the label

MODEL	LABEL	LABEL SIZE(mm)		MAX. OUTSIDE	
MODEL	GAP(mm)	STROKE	WIDTH DIAMETI	DIAMETER (mm	
APF-30	2-3	20-60	20-30	100	
APF-60			20-60		
APF-100			20-100		





The smaller the label it is when you dispense, the more troublesome it becomes It assures high performance for small labels.

The new type of a premium tool, APN10-30 assures high performance for samll labels.

- For pre-printed general roll labels. No special (punched or slit) labels or separators required.
- Supports use of label size from 10x30mm up to 60x30mm.

MODEL	LABEL GAP(mm)	LABEL S	IZE(mm)	MAX. OUTSIDE
MODEL		STROKE	WIDTH	DIAMETER(mm)
APN10-30	2-3	10-60	20-30	100

Notice

- Labels must be more than 50 µm thick for all models.
- Some types of film, synthetic paper, and other special labels may not be supported.
- Please ask our distributor for details before using special labels.
- We reserve the right to change specifications without notice for improvement.

OJP PAT. 2708677, 2708680

TOWA CO.,LTD.

Ginza YK Bldg., #10-9, Ginza 5-chome, Chuo-ku, Tokyo 104-0061, Japan Tel:+81-3-3572-9621 Fax:+81-3-3572-9620 http://www.towa.jp/export/ e-mail: export@towa-ltd.co.jp