## POLYKEN®



Backing	Backing:	1.5 mil Aluminum Foil	
- Adhesive	Adhesive:	Synthetic Rubber	
<ul> <li>Release</li> <li>Liner</li> </ul>	Liner:	Polycoated Natural Kraft Paper	
	Colors:	Aluminum	
Con voice	Specificatio	ons: UL 723 Classified	
72jo VOC3	Standard Si	Sizes: 48mm x 46M, 72mm x 46M	

## Applications

٠	Taping joints and seams in duct work for A/C,	•	General purpose industrial and automotive uses.
	heating, and ventilation systems	•	Insulation seaming and patching

Features	Benefits
Aluminum Foil Backing	<ul> <li>Conformable to fit corners and joints</li> </ul>
	UV and moisture resistant
	<ul> <li>Mold and mildew resistant</li> </ul>
Synthetic Rubber Adhesive	<ul> <li>Non-solvent for less odor and low VOC content</li> </ul>
	<ul> <li>Extreme high tack, aggressive bond to surfaces</li> </ul>
	<ul> <li>Good all-weather performance</li> </ul>
UL 723 Classified	<ul> <li>Meets flammability requirements for use in</li> </ul>
	construction and marine applications
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1</li> </ul>
	(Low Emitting Materials) under LEED®

<i>.</i> .		
Standard UOM	Metric UOM	Test Method
3.2 mils	0.081 mm	ASTM D-1000
1.5 mils	0.038 mm	ASTM D-1000
75 oz/in	8.21 N/cm	PSTC-101
11 lb/in	19.26 N/cm	ASTM D-1000
40 to 200 °F	4 to 93 °C	
0		
10		
<1 g/L		
	Standard UOM 3.2 mils 1.5 mils 75 oz/in 11 lb/in 40 to 200 °F 0 10	Standard UOM         Metric UOM           3.2 mils         0.081 mm           1.5 mils         0.038 mm           75 oz/in         8.21 N/cm           11 lb/in         19.26 N/cm           40 to 200 °F         4 to 93 °C           0         10

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

