

# LUBRICANTS

Water  
proofPRTR  
freeOSA  
free

## **NX25 SILICONE GREASE** Item Number : 00025

## **NX26 SILICONE GREASE SPRAY** Item Number : 00026

**Heat resistant · Cold resistant and Water resistant grease**

### FEATURES

- Protects rubbers and plastics from friction and degradation.
- Applicable temperature from -40 °C ~ 180°C.
- Different from common grease, no dripping at high temperature and do not get hardened at low temperature. Chemically, it is an inert product.



100 g (00025)    220 ml (00026)

### APPLICATION

- Lubrication for Disk Brakes O ring.
- Seals for coupling rubber of wheel cylinder.
- Lubrication for wiper motor.
- Lubrication for Clutch, Pilot and Bearing.
- Lubricates and seals for frictional gear parts.
- Anti-rust and water proof for battery terminal connector.



Anti-rust and water proof for battery terminals.

### PERFORMANCE

Outer appearance	Color ~ Gray brown paste
Consistency (25°C, 600W/min)	260 (No: 0025), 320 (No: 0026)
Oil Separation (150°C x 24hr, Wt%)	2.5
Heat Loss (150°C x 24hr )	2.0
Specific Gravity(25°C)	1.05
Applicable temperature	-40 °C ~ 180°C

**\*Not applicable to Silicone Rubber and Nature Rubber.**

Penetrate	High	★	Low
Pressure	High	★	Low
Anti-rust	Long	★	Short
Viscosity	High	★	Low
Adhesive	High	★	Low