

Protective One Step BW100EP

Technical Data			Date 10/2014	
Product Description	Surface Protection Film BW100EP			
Construction	Backing	Adhesive	Color	
	Polyethylene	Acrylic	Black and white	
Typical Physical Properties and Performance Characteristics	Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes. Test Method			
	Adhesion to Steel:	2.00 +/- 0.20 N/cm (500 +/- 50 gf/25mm	AFERA 4001 *	
	Total Thickness:	100 +/- 10 μm	DIN 53370	
	Breaking Strength: Machine Direction : Transverse Direction:	> 17 N/mm ² > 11 N/mm ²	DIN 53455	
	Elongation at Break: Machine Direction: Transverse Direction:	> 200 % > 350 %	DIN 53455	
			* modified for protective films	
General Information				

- Before application the surface must be free from oil, fat, dust and solvents. Best to apply at room temperature between $>10^{\circ}$ C and $< 40^{\circ}$ C.
- The product should be stored at room temperature ($< 40^{\circ}$ C).
- The product should be applied and removed within 12 months after date of manufacture.
- The product is resistant to:

-	moisture:	good
-	oil:	moderate
-	solvents:	moderate

• Protective Pro BW100EP is suitable for outdoor use up to 6-9 months

บริษัท แมทท์เรียลวัน(ประเทศไทย) จำกัด เลขผู้เสียภาษ์ TAX ID : 0105555049853 568/4 ชอยลาดพร้าว 112 (เอี่ยมสมบูรณ์) ถนนลาดพร้าว แขวงพลับพลา เขตวังทองหลาง กรุงเทพมหานคร 10310 ประเทศไทย

Application Ideas

Protective Pro BW100EP is

- Recommended for the protection of sensitive surfaces against dirt and damage during processing, storage and mounting etc.
- Protective Pro BW100EP has a Very high level of adhesion especially made to protect:
 - Rough surface such as Aluminum with Sahara finishing.
 - Varnished surfaces, acrylic- and synthetic resin varnish

Features	Advantages	Benefits
PE backing,	resistant against moisture,	prevents surface from
black and white	oil, solvents, dirt,	dirt and damage,
	mechanical abrasion	for outdoor use
Acrylic adhesive,	sticks to rough surfaces,	temporary surface protection
Very high adhesion level	cleanly removable after use	cleanly removable

IMPORTANT NOTICE TO CUSTOMER:

All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of liability relating to this product are governed be the Terms of Sale subject, where applicable, to the prevailing law.

บริษัท แมทท์เรียลวัน(ประเทศไทย) จำกัด เลขผู้เสี่ขภาษ์ TAX ID : 0105555049853 568/4 ซอยลาดพร้าว 112 (เอี่ยมสมบูรณ์) ถนนลาดพร้าว แขวงพลับพลา เขตวังทองหลาง กรุงเทพมหานคร 10310 ประเทศไทย MaterialOne(Thailand) Ltd. TAX ID : 0105555049853 568/4 Soi LatPhrao 112 (Aumsomboon), Lat Phrao Rd., Plubpla, Wangthonglang, Bangkok 10310 Thailand