

SPECIFICATIONS

PRODUCT NAME : MT-PET RED TAPE			
SURFACE MATERIAL			
ARTICLE	PET FILM	COLOR	Blue
THICKNESS (m/m)	0.038mm	SMOOTHNESS	0.060±0.005mm
PUIL-RESISTANCE (Kg/25mm)	18	PRINTABILITY	/
PRESSRURE SENSITIVE ADHESIVE			
ADHESIVE BASE	SILICON	VOLTAGE RESISTANCE (KV)	≥ 4
DRY COATING THICKNESS (m/m)	0.022±0.005	HOLDING RESISTANCE	48
DRY COATING WEIGHT	22±5	WERTHERING RESISTANCE	GOOD
INTITIAL TACK	≤ 8	TEMPERATURE RANGE	-40℃ ~180℃
PELL ADHESION (KG/25mm)	≥0.7	MAX TEMPERATURE	200℃ * 100s
LONGATION (AG BREAK%)	45	INSULATION RESISTANCE	1.0*10 ¹²
STANDARD LENGTH (m)	66	STANDARD WIDTH (mm)	500
FLAME RESISTANCE	GOOD	STOCK PERIOD	SIX MONTHS
CHEMISTRY RESISTANCE	GOOD	LIQUID RESISTANCE	GOOD
STOCK ENVIRONMENT	30℃ *60%		
USE: This product is used for printing circuit board, PC main board			